

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
5 February 2004 (05.02.2004)

PCT

(10) International Publication Number
WO 2004/011163 A1

(51) International Patent Classification: B08B 15/02,
E04H 15/50

(21) International Application Number:
PCT/US2003/023531

(22) International Filing Date: 25 July 2003 (25.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/398,914 26 July 2002 (26.07.2002) US
60/486,777 11 July 2003 (11.07.2003) US

(71) Applicant (for all designated States except US): MINTIE
CORPORATION [US/US]; 1114 San Fernando Road,
Los Angeles, CA 90065 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): MINTIE, Kevin, J.
[US/US]; 946 Calle Amable, Glendale, CA 91208 (US).
MUNOZ, Jose Guadalupe [US/US]; 16608 Kelwood
Street, Valinda, CA 91744 (US).


(74) Agent: WARD, Richard, J., Jr.; Christie, Parker & Hale
LLP, P.O. Box 7068, Pasadena, CA 91109-7068 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BE, BG, BR, BY, BZ, CA, CH, CN, CU, CZ, DE,
DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: ENVIRONMENTAL CONTROL UNIT



(57) Abstract: A portable enclosure (10), easily erectable and collapsible, to provide environment control and prevent contaminants from being released from the enclosure. The enclosure provides a flexible envelope (50) attached to the interior of the space defined by vertical and horizontal supports (12, 16, 17) which can be erected and collapsed. When erected the enclosure functions as an anteroom and has removable panels in the sides and top. In use, the enclosure is sealed against a vertical or horizontal surface to be worked on (57) and a panel (52) from the side of the enclosure is opened and closed to provide access to the surface by the user. When collapsed the enclosure is a package approximately the size of an average golf club bag which is easily portable to another location. Ducting (66, 68) is provided to which negative pressure pumps are connected to maintain negative pressure within the enclosure and draw contaminants into the pump and then into a closed container. In one embodiment, a four-sided flange (144) extends from the rear side of the enclosure to allow sealing of the flange around the doorway and thereby provide a mechanism for isolating the room located interiorly of the doorway.

WO 2004/011163 A1

BEST AVAILABLE COPY



European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

1

ENVIRONMENTAL CONTROL UNIT

5 SUMMARY OF THE INVENTION

10 The present invention relates to a portable collapsible apparatus for use in hospitals, healthcare facilities, clean rooms and other interiors for creating a controlled localized environment which is isolated from the surrounding environment. The unit is particularly useful in applications involving construction and maintenance in ceiling cavities, wall cavities and other spaces in which plumbing, wiring, ducting and the like are located.

15 In another embodiment, the invention relates to an apparatus for attachment to an entry to a room for sealing and isolating the room to prevent the spread of infectious organisms and other airborne particulates from the interior of the room to the surrounding areas outside the room.

20 BACKGROUND OF THE INVENTION

Construction and maintenance projects in a hospital provide great potential for releasing contaminants and airborne particulates that can lead to infections or other forms of contamination. All buildings, including hospitals harbor biological pathogens in the cavities of walls, floors and ceilings. Whenever these cavities are penetrated and the air in them is disturbed, the risk of aerosolizing these pathogens is high. There are always air currents in these cavities, even those that are considered dead air spaces. When an opening is made, the air currents change and pathogens are introduced into the occupied space.

30 Routine maintenance and repair activities such as opening a ceiling tile or a wall to check or test equipment for elevator operation, electrical wiring, pneumatic tube systems, plumbing or air conditioning can release harmful organisms into the environment.

An infectious containment and environmental monitoring program must be established to eliminate or minimize the

1

incidence of infectious particulates, dust, and other
airborne particulates associated with construction and
5 repair projects in healthcare facilities and other clean
room type environments. Every organization must assess the
level of protection needed for the various construction,
repair, replacement, and maintenance activities that will be
undertaken in the facility. This assessment allows the
10 facility to tailor the level of protection to its specific
needs. In addition to having an application in hospital
environments, the present invention is also highly useful
and applicable for applications in such areas as asbestos
removal and removal of other possible airborne contaminants
15 in many other types of facilities.

Various types of enclosures have been provided in the
past for isolating a work area from the surrounding
environment. An example of an isolation enclosure is
provided in U.S. 5,558,112. This patent discloses a
20 portable isolation enclosure apparatus for removing material
from the walls of a building while isolating a portion of
the wall from which the material is being removed. The
apparatus is positioned against a wall such that an area of
the wall is isolated from the ambient environment, and is
25 disposed with the open side of the enclosure facing the wall
such that a worker inside the enclosure can access the wall.

In Reissue 33,810 an isolation enclosure is provided
for removing asbestos material from ceilings and other
elevated asbestos containing structures. The enclosure
30 includes a booth and an adjustable plenum for being raised
and lowered relative to the booth to reach the heights of
different ceilings. A curtain is provided which extends
from the bottom of the plenum below the top of the booth to
maintain a closed environment. The enclosure is provided
35 with vacuum and ventilation systems for filtering and
ventilating the air which is drawn into the enclosure.

In U.S. 4,682,448, an enclosure is provided for working
on ceiling openings. The apparatus provides an enclosure

1

extending from the floor to the ceiling and enabling access through a ceiling opening for above ceiling construction and/or repair while providing a isolated enclosure for preventing pathogens, dust, asbestos and other debris from being allowed to escape into the surrounding environment. Another example of a prior art enclosure is shown in U.S. 5,062,871.

10

SUMMARY OF THE PRESENT INVENTION

The present invention provides a portable collapsible environmental control apparatus that includes a framework having a first set of vertical supports and a collapsible horizontal support element extending between vertical supports at the base of the vertical supports. First collapsible supports extend between a pair of adjacent vertical supports along the lengthwise dimension of the enclosure. Second collapsible supports extend between a pair of adjacent vertical supports along the widthwise dimension of the enclosure.

Sliders are mounted on each vertical support and are connected to a bottom portion of each of the first and second collapsible supports.

A flexible collapsible gas impermeable containment envelope is secured to the interior of the apparatus and encloses the top sides and bottom of the enclosure wherein the vertical supports can be raised to ceiling level and held in position against the ceiling to create a controlled environment within the control apparatus.

BRIEF DESCRIPTION OF THE DRAWINGS

The features of the invention and additional details of the apparatus according to the present invention will be more fully understood by reference to the figures of the drawing wherein:

1

FIG. 1 is a perspective view of a fully opened enclosure according to the present invention prior to vertical extension and movement into an operating position;

5

FIG. 2 is a photocopy of the enclosure according to the present invention after full vertical extension with the top of the enclosure abutting the ceiling;

10

FIG. 3 is a photocopy of the enclosure of the present invention in a fully collapsed configuration before placement in a storage container;

FIG. 4 is a photocopy of the enclosure of the present invention in its fully collapsed and folded condition in a storage container for ready portability;

15

FIG. 5A is a front elevation view of an alternate embodiment of the enclosure for providing access from all four sides of the enclosure;

FIG. 5B is a side elevation view of the embodiment of FIG. 5A taken from the left side of the enclosure;

20

FIG. 5C is a top view of the enclosure illustrating a flange enhancement extending from the rear of the enclosure;

FIG. 6A is a rear elevation view of the enclosure shown in the preceding figures illustrating the positioning and rectangular configuration of the flange;

25

FIG. 6B is a side view of the enclosure taken from the side opposite FIG. 5B; and

Fig. 7 is a view of the top of the enclosure illustrating a removable section to provide an opening when the enclosure is raised against a ceiling;

30

FIG. 8 is a diagram illustrating placement of the enclosure of the present invention outside a patient room to isolate the space within the room from the surrounding environment.

35

DETAILED DESCRIPTION OF THE INVENTION

The present invention comprises a rectangular enclosure which comprises a plurality of hollow vertical frame members 12 and a first pair of horizontal frame members 16

1

located at the bottom of the enclosure extending along the front and rear lengthwise dimension of the enclosure. A second pair of horizontal frame members 17 join adjacent members 12 along the left and right widthwise dimension of the enclosure.

In the middle of the horizontal frame members 16, a hinge 18 is provided which is actuated vertically in an upward direction when the enclosure is collapsed into its folded position. A similar pair of hinges 20 are provided in the frame members 17 and these likewise pivot upwardly when the enclosure is collapsed. Adjacent vertical frame members in the lengthwise dimension are joined by a truss 22 on the front and rear of the enclosure which comprises a series of hinged articulated arms 24 extending between the vertical frame members 12. A set of second trusses 26 each comprising cross arms 28 join adjacent vertical members 12 along the left and right widthwise dimension of the enclosure. The lower arm of each truss is connected to a movable slider 49 which slides up and down vertical member 12 as the enclosure is opened and collapsed. When the unit is collapsed into its folded and closed position, trusses 22 and trusses 26 close in an accordion action to permit the vertical frame members 12 to be moved toward each other until they are closely spaced in the closed position.

A removable and collapsible rectangular upper frame 30 having downwardly extending legs 32 is positioned above the vertical frame members and the legs 32 are telescopically received within the vertical frame members 12. The top of the upper frame member 30 engages the ceiling when the enclosure is in its raised and fully deployed position to permit the removal of one or more ceiling tiles directly above the enclosure and within the perimeter of the enclosure prior to work being done in the ceiling cavity. A nonporous foam bumper 34 extends around the periphery of upper frame member 30 to closely engage the ceiling and adopted to be pressed by spring compression against the

1

ceiling to achieve a tight seal against the ceiling while the enclosure is used for work operations in the area above the ceiling. Outer leg caps 36 are provided at the top of the frame members 12 for receiving the downwardly extending legs 32 of the upper frame member 30. Set screws 31 are provided in the outer leg caps for tightening the leg caps against the legs 32 of the frame member to hold and lock the frame member 30 in a desired positions.

10

In FIG. 1 one of the vertical frame members 12 is shown with a portion broken away so as to illustrate a compression spring 40 located in the hollow interior of the frame member and seated within the vertical frame member 12 supporting the bottom of leg member 32 of the upper frame member 30. Similar compression springs are provided in each of the other three vertical frame members of the enclosure to provide spring compression for pressing the foam bumper 34 of the upper frame member to seal against the ceiling when the enclosure is fully extended vertically and abuts the ceiling in readiness for use.

15

20

Legs 32 are telescopically received within outer leg caps 36 and seat on top of compression springs 40. Compression springs 40 in turn are supported by sliders 49 which are mounted on top of frame members 12. Frame members 12 comprise an outer leg 42 and an inner leg 46. As shown in FIG. 1, the enclosure is in its retracted position in the sense that the upper frame member is at its lowest elevation and the hollow outer legs 42 receive vertically extending inner legs 44. A collar 46 is located at the bottom of outer legs 42 and provides a mounting for a pull pin or a set screw 48. When it is desired to raise the enclosure to the ceiling, an operator grasps the outer legs and raises the outer legs to the desired height. When the desired height is achieved, set screws 48 are extended inward and engaged with the inner legs 44 to lock the assembly in position. By exerting upward force on legs 42, bumper 34

30

35

1 50818/RJW/M425

engages and bears against the ceiling with springs 40 being compressed to make a releasable seal against the ceiling.

5 The closed interior of the enclosure is provided by a containment envelope 50 fabricated of a impermeable material such as vinyl or plastic sheeting. Provided at one side of the enclosure and incorporated into the envelope is a zippered entrance 52 which is used by a worker to enter and
10 leave the enclosure. After a worker enters the enclosure the entrance covering is zipped closed to provide a totally enclosed compartment within the enclosure. Two windows 54 are provided on either side of the envelope to permit light to enter the enclosure and to permit the occupant inside the
15 enclosure to see the exterior and to permit others on the outside of the enclosure to observe the occupant on the interior.

The envelope 50, in one exemplary embodiment, is supported by a plurality of cuffs 56 which encircle the
20 vertical frame members 12 and which are secured to the envelope at spaced intervals by clips, Velcro connectors, snaps and the like. The envelope extends around the entire enclosure and across the entire bottom of the enclosure. It is secured to the top of the upper frame by Velcro or snap
25 fasteners. When the upper frame is raised, the cuffs slide up the outer legs extending the envelope so that the closed environment of the enclosure is maintained.

Shown at one side of the enclosure is a first duct 66 to which a HEPA vacuum is connected so that any
30 contaminants, pathogens and the like which enter the enclosure are drawn out through duct 66 into a filtering apparatus 70 (see FIG. 8). A second duct 68 is shown adjacent to duct 66 to which is connected a vacuum pump for creating a negative pressure within the enclosure to cause
35 any contaminants to be drawn downwardly and into the filter apparatus.

The enclosure 10 is shown in its fully extended configuration in FIG. 2. Upper legs 42 are raised to the

1

desired height and held in position on lower legs 44 by means of set screws. Alternatively pins 51 such as cotter pins can be used and inserted into apertures 53 to hold the upper portion of the enclosure at the desired height. Sliders 49 are locked into position at the top of frame members by spring loaded pins (not shown). The upper portion of the envelope 55 is connected around the interior of frame 30. Frame 30 is then raised to engage the ceiling 57 as shown in phantom in FIG. 2. The frame 30 is spring-loaded and held in position by set screws 31 or alternatively pins and aperture. Window 54 is shown in FIG. 2 as is a pocket 59 for storing instructions, specifications and other information pertinent to the work to be performed while using the enclosure.

The specific configuration of the containment envelope is related to the application for which the enclosure is used. The configuration can be tailored for wall access projects, ceiling cavity projects, as an anteroom for construction areas and for use in converting conventional patient rooms into isolation rooms.

When it is desired to move the enclosure or to store it, the set screws are loosened, the upper frame is lowered into the position shown in FIG. 1, and the envelope is allowed to drop and settle toward the bottom of the enclosure. The upper frame member 30 is then removed from the top of the enclosure. Hinges 18 and 20 are caused to pivot upwardly to bring the sides of the enclosure toward each other. At the same time, trusses 22 compress, sliders 49 move downwardly along frame members 12, and the arms of the truss approach a near vertical position in the totally folded condition. Similarly, the truss arms 28 of truss 26 scissor together to near vertical position. Provided at one side of the enclosure are a pair of wheels 64 which allow the unit to be tilted when it is folded so that it can be rolled to another position or rolled into a storage location. The upper frame member 30 is hinged at the

1

corners to permit closing into a compact elongated configuration.

5 After collapsing the enclosure into the configuration shown in FIG. 3, the apparatus is enclosed by drawing a fitted cover 61 over the top of the apparatus and then downwardly to the bottom of the apparatus. One or more belts 63 are provided to cinch the covering around the
10 apparatus and hold the apparatus in a compact package. Wheels 84 at the bottom of the apparatus permit the apparatus to be rolled to a new location enhancing the portability of the apparatus.

Another embodiment of the environmental control unit of
15 the present invention is illustrated FIGS. 5A, 5B and 5C. As shown in FIG. 5A, the enclosure comprises the enclosure 10, a four-sided flexible envelope 102 mounted on vertical supports 104 by means of a series of snap cuffs 106 which are attached to the outer periphery of the envelope and are
20 also attached to the vertical supports. FIG 5A illustrates the primary entry side of the enclosure. As shown therein it includes a door panel 108 which is secured in place by means of a zipper 110. The direction of travel of the zipper is shown by arrow 112. The zipper extends around the
25 entire periphery of the panel to permit removal of the door panel. Likewise, the zipper can be stopped at stop 114 and if desired it can be rolled up and retained by Velcro straps 116 to provide full access to the interior of the envelope.

The door panel has a clear vinyl window 118 provided in
30 the center thereof and below it is a pouch 120. An upper portion 122 of the enclosure is height adjustable along the vertical supports which gives the basic four sided outline to the enclosure. The envelope is secured by a plurality of cuffs 124 which are closely spaced as shown in FIG. 5A.
35 When it is desired to adjust the height of the enclosure, the upper portion 122 is extended upwardly and the cuffs are slidably moved on the vertical supports to allow the upper portion to be extended until it reaches the desired height,

1

typically coming into contact with a ceiling or ceiling tiles.

5 The door panel 108 is of a flexible material as is the rest of the enclosure to permit it to be rolled up when unzipped and to also permit it to be collapsed with the rest of the enclosure when the enclosure is collapsed down into a size for easy portability

10 In FIG. 5B, the left side of the enclosure shown in FIG. 5A is illustrated. As shown therein it comprises a flexible side wall 126 and contained within it is a panel 128 secured in the side wall by means of a zipper 130. The direction of travel 132 of the zipper is shown and similar
15 to door panel 108, the side panel 128 is "zip out" in configuration and can be either removed or flipped open when the zipper is traversed around at least three sides of the side panel. A vinyl window 134 is provided in the side panel and at the base of the vinyl window is a negative air vent 136. The panel 128 can be used to function as a door
20 by stopping the zipper at stop 138 to create a door opening.

 Below the window is located a zip-out panel 140 which includes ducts 142, 143 to which are connected pumps and
25 other evacuating equipment which are utilized to maintain a predetermined air pressure within the enclosure and to withdraw any contaminants which enter the enclosure and communicate such contaminants into a closed container connected to a pump to prevent escape of any contaminants to the atmosphere outside of the enclosure.

30 Referring now to FIG. 5C, a view taken from the top of the enclosure, the rectangular outline of the enclosure is clearly illustrated as are representative slidable cuffs 124. Ducts 142, 143 appear at the side. Extending from the rear is a flange 144 which is slightly flared outwardly from
35 the enclosure and is rectangular in elevation and is secured to the rear side of the enclosure 10 as will be more fully disclosed in conjunction with the discussion of FIGS. 6A and 6B. The flange is secured in an air-tight manner to the

1

rear side of enclosure 100 and extends outwardly. The flange 144 is of the same flexible material as the envelope 102 and can be securely attached around a door frame so as to seal the entire periphery of the door frame and thereby seal off the room inside from the atmosphere on the outside of the envelope. When the flange is secured around the door frame to a room such as a patient's room, the functionality of the enclosure is as an anteroom sealed to the entry into the room to provide a mechanism for isolating the room to which the enclosure is attached.

This is particularly important and useful in hospitals and healthcare environments when a serious risk of air borne infection is present and the patient and the room in which the patient is located needs to be isolated from the rest of the environment outside the patient's room. In a typical configuration, the rectangular flange 144 is three to four feet wide, six to seven feet and twelve to twenty inches deep high so as to easily fit around the entire periphery of a typical doorway.

These aspects of the enclosure will be further understood by reference to FIGS. 6A and 6B in which FIG. 6A is an elevation view of the wide side of the enclosure opposite the side shown in FIG. 5A. As shown therein, this side of the enclosure has two zippered panels. The first being panel 146 which is slightly larger than the periphery of flange 144 and is secured around it periphery by a zipper 148. Extending the zipper around the entire periphery of panel 146 permits its removal together with the flange 144 and an inner zip-out panel 148. Second zip-out panel 148 is located interiorly of the periphery of the flange 144 and includes a clear flexible vinyl window 150 and below it a pouch 152 into which information, messages, charts, other materials related to the use of the enclosure can be placed. The two zipper arrangement provides complete flexibility allowing panel 148 to be removed when the flange is in place and sealed to the periphery of a door way to a room

1

5

10

15

20

25

30

35

permitting the use of the enclosure as a means of maintaining isolation of the room which still permits entry and exit of medical personnel, etc. A person desiring entry into the room to which the enclosure is attached would first unzip panel 108 on the front and then reinstall it to completely close the interior of the environmental control enclosure. Once that has been established and the negative atmosphere created and sterilized, door panel 148 is approached and the party desiring entry into the room, for example to treat a patient, unzips panel 148 and enters the patient's room. The steps in reverse are followed when a party leaves the patient's room.

Referring now to Fig. 7, a top view of another embodiment of an enclosure according to the present invention. As shown therein, the top 160 includes a removable zippered panel 162. A zipper 164 is utilized to attach and detach the panel from the top 160. This structure enables the envelope to function when the user is working in ceiling cavities. The top portion of the enclosure is height adjustable in a range from approximately 7 feet to approximately 11 feet in height. In use it is brought into position and the top portion extended to contact and be sealed against the ceiling. Panel 162 is zipped out and the user has access to the ceiling tiles and the ceiling cavity beyond.

The enclosure of the present invention has multiple applications. It can be used to provide an anteroom for construction and maintenance projects in walls and ceilings in patient occupied areas. It is engineered to provide a negative pressure entry and exit chamber. Doors can be provided in all four sides for greater flexibility. Negative air ports can be switched from one side to the other. A flange can be attached around a door frame and when sealed prevents contaminants from escaping the enclosure. When used to isolate a patient's room, the enclosure provides a convenient, quick, safe conversion of

1

5

patient room into an isolation room by creating an anteroom "airlock" between the room and the outside corridor into which the room opens.

10

The diagram of FIG. 8 illustrates the use of the enclosure according to the present invention as a mechanism for providing isolation of a room such as a patient's room in a hospital. The present invention enables rapid conversion of a room into an isolation room. As shown therein, a conventional patient room 170 is furnished with a bed 172 and typically has a doorway 174 for entry into the room and a bathroom 176 which is connected to room 170 by a second doorway 178.

15

20

25

30

To isolate patient room 170, an enclosure 180 according to the present invention is placed adjacent doorway 174. The embodiment of the invention shown in FIGS. 5 and 6 is utilized with the flange attached around the periphery of the doorway and sealed to the periphery to prevent airborne particulates from escaping from the enclosure 180. In effect, the enclosed provides an "airlock" between the room 170 and the corridor outside. A HEPA filtered negative air machine 182 is connected to duct 184 to complete the conversion and isolation. Typically the machine provides negative air pressure of a minimum of 300 CFM prescribed by the requirements of the Centers for Disease Control and Prevention. The result is an important tool, particularly useful in dealing with emergency situations requiring quick conversion of a conventional room to an isolated room to prevent the spread of infection to other areas of the healthcare facility.

35

1

WHAT IS CLAIMED IS:

5

1. A portable collapsible environmental control apparatus comprising:

a framework having a set of extendable vertical supports, a collapsible horizontal support element extending between vertical supports at the base of the second vertical supports,

10

first collapsible supports extending between a pair of adjacent vertical supports along the lengthwise dimension of the enclosure,

15

second collapsible supports extending between a pair of adjacent vertical supports along the widthwise dimension of the enclosure,

a plurality of sliders mounted on each vertical support and connected to a bottom portion of each of the first and second collapsible supports and

20

a flexible collapsible containment envelope secured to the interior of the framework and extending from the top of the enclosure downward to enclose the sides and bottom of the enclosure wherein the vertical supports can be raised to ceiling level and held in position against the ceiling to create a controlled environment within the control apparatus.

25

30

2. A control apparatus according to claim 1 comprising a first and second set of vertical supports, the second set being telescopically received in the first set.

35

3. An apparatus according to claim 2 including a collapsible horizontal frame adapted to telescopically engage the vertical supports removably mounted at the top of the framework.

4. A control apparatus according to claim 3 wherein the envelope is open at the top to facilitate working in ceiling cavities.

1

5. A control apparatus according to claim 4 including a removable opening in a vertical side of the envelope to permit ingress and egress of a worker when the enclosure is placed in working relation with a ceiling cavity.

6. A control apparatus according to claim 5 including at least one duct extending through the envelope from the interior to the exterior of the enclosure.

7. A control apparatus according to claim 6 having a filter apparatus connected to the duct for collecting airborne particulates drawn into the enclosure.

8. A control apparatus according to claim 7 including a second duct extending through the envelope from the interior to the exterior of the enclosure.

9. A control apparatus according to claim 8 having a negative air machine connected to the second duct for creating negative air pressure within the enclosure.

10. A control apparatus according to claim 9 wherein a pair of wheels are attached to the enclosure at the base of the framework to facilitate moving the apparatus in the collapsed condition.

11. A portable collapsible environmental control apparatus comprising:

a collapsible framework including extendable and retractable vertical and horizontal supports,

a closed flexible impermeable envelope secured to the framework on the interior thereof, the framework and envelope when in the fully erected condition defining a working enclosure of sufficient interior size to permit a fully erect worker to function; and

a four sided extension attached to a side of the

1

envelope adapted to be sealably attached around a door opening to isolate the environment of a room within.

5

12. A control apparatus according to claim 11 having at least one removable access panel in the envelope to permit access to and from the enclosure.

10

13. A control apparatus according to claim 12 having at least one transparent section in the side of the envelope to permit viewing into and out of the enclosure.

15

14. A control apparatus according to claim 13 having at least one part port in the side of the envelope for the attachment of air pressure reducing equipment.

20

15. A control apparatus according to claim 12 wherein the access panel is in the side of envelope opposite the four-sided extension.

25

16. A control apparatus according to claim 12 wherein two or more removable access panels are provided in the sides of the envelope.

17. A control apparatus according to claim 12 wherein the removable panel is provided in the top of the envelope.

30

18. A control apparatus according to claim 14 wherein the port is mounted in a removable panel.

35

FIG. 1




FIG. 2






FIG. 3

FIG. 4







FIG. 7




FIG. 6B




FIG. 6A





FIG. 8



INTERNATIONAL SEARCH REPORT

International Application No.

PCT, JJ 03/23531

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 B08B15/02 E04H15/50

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B08B E04H

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 706 551 A (SCHOFIELD PAUL S) 17 November 1987 (1987-11-17) abstract; figures column 1, line 24 - column 4, line 22 column 7, line 23 - column 10, line 37	1-3, 5, 11-13, 15, 16
Y	column 11, line 10 - line 43	4, 6-10, 14, 17, 18
Y	US 4 866 833 A (WARD ALEC D) 19 September 1989 (1989-09-19) abstract; figures 1-5, 13 column 5, line 9 - line 43	4, 17
	US RE33810 E (STRIETER J) 4 February 1992 (1992-02-04) cited in the application the whole document.	6-10, 14, 18



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
 E earlier document but published on or after the international filing date
 L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
 O document referring to an oral disclosure, use, exhibition or other means
 P document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
 X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
 Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
 Z document member of the same patent family

Date of the actual completion of the international search

11 December 2003

Date of mailing of the international search report

17/12/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax (+31-70) 340-3016

Authorized officer

Plontz, N

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT, US 03/23531

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
US 4706551	A	17-11-1987	DE	3566285 D1	22-12-1988
			EP	0178091 A1	16-04-1986
			GB	2165276 A , B	09-04-1986
US 4866833	A	19-09-1989	GB	2183268 A	03-06-1987
			EP	0226335 A1	24-06-1987
US RE33810	E	04-02-1992	US	4765352 A	23-08-1988

THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)